



267U



2600

## HOPPE Marseille 1138 Series

Lever on Type 42K Rose (Sprung & Unsprung) & Lever on Type 267U & 2600 Backplate (Sprung)

### Application

- Suitable for heavy duty public & commercial use

### Features

- Please specify at time of ordering the door thickness range required
- Door Thickness Range 35mm to 45mm (for 30 minutes Fire Door)
- Door Thickness Range 45mm to 55mm (for 60 minutes Fire Door)
- Supplied complete with bolt through & wood screw fixings

**Quick-Fit** Available with HOPPE Quick-Fit connection

### Finishes

- SAA (HOPPE F1 finish)

### Standards and certification



**Quality & Performance:** Successfully type tested to all the requirements of EN1906:2002 Grade 3 (Test reports/certificates are available on request)

**\*Note: This classification only applies to the sprung lever on round rose version. The unsprung lever has a U in digit 8**

3	7	-	1*	1	4	0	B
---	---	---	----	---	---	---	---



**Fire Safety:** Included on a successful fire test to BS EN1634 Part1. Assessed for use on 30 and 60 minutes fire doors



**Conformity Statement:** This product satisfies the dimensional recommendations contained within BS8300:2009 for Lever Handles. However the product alone does not give full compliance to BS8300 and consideration must be given to other installed hardware on the doorset.

**Guarantee:** 10 year operational guarantee