



HOPPE Paris Series – 138S/42K (Grade 4 BS EN1906:2002)

Lever on Round Rose Ø 19mm or Lever on Backplate (267U & 2600)

Application

- Suitable for extreme duty public & commercial use



267U

Standards and certification



Quality & Performance: Successfully type tested to all the requirements of BS EN1906:2002 Grade 4 (Test reports/certificates are available on request)

***Note: This classification only applies to the sprung lever on rose version**

4	7	-	1*	1	4	0	A
---	---	---	----	---	---	---	---



Fire Safety: Included on a successful fire test to BS EN1634 Part1. Assessed for use on 30 and 60 minutes fire doors



Conformity Statement: This product satisfies the dimensional recommendations contained within BS8300:2009 for Lever Handles.

Guarantee: 10 year operational guarantee



2600



HOPPE Paris 138S Series (AR200S Range)

Lever on Type 42K Rose & Lever on Type 267U, 2600, 304L & 306
Backplate Ø 19mm or Ø 22mm (Sprung & Unsprung)

Application

- Suitable for heavy duty public & commercial use

Features

- Supplied with both bolt through and wood screw fixings
- Longer spindles available for bigger door thicknesses

Finishes

- SAA (HOPPE F1 finish)



267U



2600



306



304L

Standards and certification



Quality & Performance: Successfully type tested to all the requirements of EN1906:2010 Grade 3 (Test reports/certificates are available on request)

***Note: this classification only applies to the 19mm sprung versions marked with an asterisk**

3	7	-	1*	1	4	0	A
---	---	---	----	---	---	---	---



Fire Safety: Included on a successful fire test to BS EN1634 Part1. Assessed for use on 30 and 60 minutes fire doors



Conformity Statement: This product satisfies the dimensional recommendations contained within BS8300:2009 for Lever Handles.

Guarantee: 10 year operational guarantee