



HOPPE Grade 316 Stainless Steel Furniture

AR363: Ø 19mm Straight Lever on 6mm or 8mm Round Rose, Stainless Steel Underplate (Sprung & Unsprung)

Application

- Suitable for heavy duty public and commercial use

Features

- Supplied with both wood screw and bolt through fixings
- Suitable for 40mm to 50mm door thickness
- Longer spindles are available to suit 54mm thick doors

Finishes

- Available in satin or polished stainless steel

Standards and certification



Quality & Performance: Successfully type tested to all the requirements of EN1906:2002 Grade 3 (Test reports/certificates are available on request). NOTE: The classification shown is for the sprung version. Unsprung versions have a "U" in digit 8

| | | | | | | | |
|---|---|---|----|---|---|---|---|
| 3 | 7 | - | 1* | 1 | 4 | 0 | B |
|---|---|---|----|---|---|---|---|



Fire Safety: Included on a successful fire test to BS EN1634 Part1. Assessed for use on 30 minutes and 60 minutes timber doors and 240 minutes on steel doors



HOPPE Grade 316 Stainless Steel Furniture

AR369: Ø 19mm Curved Lever on 6mm Rose (Sprung)

Application

- Suitable for heavy duty public and commercial use

Features

- Supplied with both wood screw and bolt through fixings
- Suitable for 40mm to 50mm door thickness
- Longer spindles are available to suit 54mm thick doors

Finishes

- Available in satin or polished stainless steel

Standards and certification



Quality & Performance: Successfully type tested to all the requirements of EN1906:2002 Grade 3 (Test reports/certificates are available on request)

| | | | | | | | |
|---|---|---|----|---|---|---|---|
| 3 | 7 | - | 1* | 1 | 4 | 0 | B |
|---|---|---|----|---|---|---|---|



Fire Safety: Included on a successful fire test to BS EN1634 Part1. Assessed for use on 30 minutes and 60 minutes timber doors and 240 minutes on steel doors