



HOPPE Paris Series – K138

AR600: Ø 21mm Steel Cored Lever on Type 15K Round Rose (Unsprung)

Application

- Suitable for medium duty public and commercial use

Features

- Spring cassettes available
- Supplied with wood screw fixings
- Suitable for 38mm to 47mm door thickness

Finishes

- Available in 10 RAL colours (see guide to finishes)

Standards and certification



Fire Safety: Included on a successful fire test to BS EN1634 Part1. Assessed for use on 30 minutes and 60 minutes timber fire doors



Conformity Statement: This product satisfies the dimensional recommendations contained within BS8300:2009 for Lever Handles.

Guarantee: 10 year operational guarantee



AR600: Ø 21mm Steel Cored Lever on Type 353K Radiused Plate (Unsprung)

Application

- Suitable for medium duty public and commercial use

Features

- Supplied with wood screw fixings
- Suitable for 38mm to 47mm door thickness

Finishes

- Available in 10 RAL colours (see guide to finishes)

Standards and certification



Conformity Statement: This product satisfies the dimensional recommendations contained within BS8300:2009 for Lever Handles.

Guarantee: 10 year operational guarantee



AR600: Ø 21mm Steel Cored Lever on Type 202K Rectangular Plate (Unsprung)

Application

- Suitable for medium duty public and commercial use

Features

- Supplied with wood screw fixings
- Suitable for 38mm to 47mm door thickness

Finishes

- Available in 10 RAL colours (see guide to finishes)

Standards and certification



Conformity Statement: This product satisfies the dimensional recommendations contained within BS8300:2009 for Lever Handles.

Guarantee: 10 year operational guarantee