



HOPPE Marseille Series EX1138Z (Grade 316 Stainless Steel)

Lever on Type E42K Rose (Sprung)

Application

- Suitable for heavy duty public and commercial use

Features

- Laser welding on neck of lever for heavy duty operation
- Supplied with two 4mm bolt through fixings giving stronger, more secure fixing alleviating the need for grub screw into lever neck
- Supplied with 8mm x 125mm full profile spindle (680092)
- Available in door thickness versions from 35mm to 75mm
- Longer spindles available for thicker doors.

Standards and certification



Quality & Performance: Successfully type tested to all the requirements of EN1906:2002 Grade 3 (Test reports/certificates are available on request)

3	7	-	1*	1	4	0	B
---	---	---	----	---	---	---	---



Fire Safety: Included on a successful fire test to BS EN1634 Part1. Assessed for use on 30 minutes and 60 minutes timber fire doors and 240 minutes on steel doors.



Conformity Statement: This product satisfies the dimensional recommendations contained within BS8300:2009 for Lever Handles.

Guarantee: 10 year operational guarantee



HOPPE Grade 316 Stainless Steel Furniture

AR361: 19mm or AR362: 22mm Return to Door Lever on 6mm or 8mm Round Rose, Stainless Steel Underplate (Sprung) Grade 3

Application

- Suitable for heavy duty public and commercial use

Features

- Available in 6mm or 8mm Roses
- Available in either sprung or unsprung versions
- Supplied with both wood screw and bolt through fixings
- Suitable for 40mm to 50mm door thickness
- Longer spindles are available to suit 54mm thick doors

Finishes

- Available in satin or polished stainless steel

Standards and certification



Quality & Performance: Successfully type tested to all the requirements of EN1906:2002 Grade 3 (Test reports/certificates are available on request). NOTE: The classification shown is for the sprung version. Unsprung versions have a "U" in digit 8

3	7	-	1*	1	4	0	B
---	---	---	----	---	---	---	---



Fire Safety: Included on a successful fire test to BS EN1634 Part1. Assessed for use on 30 minutes and 60 minutes timber doors and 240 minutes on steel doors



Conformity Statement: This product satisfies the dimensional recommendations contained within BS8300:2009 for Lever Handles.

Guarantee: 10 year operational guarantee