



Mortise lock **with roller bolt**, prepared for profile cylinder, zinc plated lock case, adjustment range of latch bolt 8-16 mm, 1 turn, top and bottom of lock case closed. Certified as per EN 12209.

1452						Standard designs and special designs	
Backset in mm	25	30	35	40	45	Forend 22 mm	<input type="checkbox"/>
Widths in mm	40	45	50	55	60	U-shaped forend 22 or 24 mm	<input type="checkbox"/>
Dead bolt throw 20 mm				<input checked="" type="checkbox"/>		Controlled latch bolt stop (FS approval not applicable)	-
Follower in mm		8	9	10		Prepared for RZ 22 (swiss standard)	<input type="checkbox"/>
Reversible latch bolt				-		Dead bolt monitoring device including 10 m cable	<input type="checkbox"/>
Latch bolt extended				-		Follower monitoring device including 8 m cable	-
Dead bolt extended 3 or 5 mm				<input type="checkbox"/>		Refurbishment forend 380 mm	-
Forend steel zinc plated				<input checked="" type="checkbox"/>		Fire doors	-
Latch and dead bolt nickel-plated				<input type="checkbox"/>		For burglar resistance doors according to EN 1627 RC2	-
Forend 24 mm				<input checked="" type="checkbox"/>		Matching striking plates on page	209

Standard design Special design

Forend stainless steel, latch and dead bolt nickel plated